

## Ekahau B4

# Wi-Fi Badge Tag for Real-Time Locating

The Ekahau B4 badge tag provides accurate location for tracking people within your enterprise using your existing Wi-Fi network. These badges are the same size and shape of typical ID badges to fit easily on a lanyard with other credential cards or on a belt clip.

The Ekahau B4 enables easy two-way communication between staff members helping organizations increase staff productivity and safety. The Ekahau Real-Time Location System (RTLS) gives key staff members the information they need using contextaware (such as tag button press, location, or proximity) and condition-aware (item category, count, or temperature) business rules. The badge incorporates a self-illuminating OLED (organic LED) display for sending alerts and receiving text messages. This distinguishing feature enables staff to communicate for routine or emergency reasons to offer to enhance on-the-job safety for staff members and others that may be impacted. Ekahau RTLS provides an easy-to-use web-based user interface that displays the location of people wearing the Ekahau B4 in an actual, floor plan view. The text messaging capability, combined with accurate real-time location data, provides a powerful way to remotely manage large areas, workflows, and a high volume of people, and the workflow of large numbers of people.

#### Two-way Communication and Custom Buttons

This small, two-way device is an ideal way to improve staff security. Using the Ekahau B4, a staff member is able to send an alert if being attacked or if immediate help is needed. In addition, a built-in motion sensor enables automated "man down" alarms. The alarm, which reveals the precise location of the badge at the time of the alert, can be programmed to call security, re-point video cameras, or control door locks and lighting—all customized to your environment.

The badges use a high-energy, rechargeable battery that works for weeks (depending on location update interval) without recharging. The battery can be charged using individual desk chargers or a rack charger, which can charge up to 10 tags at a time.



## **Features**

- Designed for staff or visitor location awareness applications
- Hands-free safety pull for staff duress
- Programmable buttons for customized messaging
- Remotely-activated audio buzzers and two LEDs for on-board alerting
- Includes environmentally-friendly rechargeable batteries

### **Benefits**

- Accurately track, staff, visitors, and other personnel
- Reduce response times with Ekahau's exclusive two-way communication features
- Send and receive messages to and from any badge within your Wi-Fi environment
- Customize alarms and notifications with two call buttons
- Stay powered with rapid two hour charge

# Technical Specifications

#### Radio

Supported Wi-Fi Networks: 802.11 b/g DSSS (Direct Sequence Spread Spectrum)

Media Access: CSMA/CA Output Power: +12dBm

Receiver Sensitivity: -93dBm@1Mbit/s FCC, Canada, ETSI 2.4 - 2.4835 GHz

Japan 2.471 -2.497 GHz

Network Protocol: UDP/IP, addressing DHCP or static Security: WEP 40/104bit (equals 64/128bit), WPA2-PSK

#### **Electrical Interface**

DC Power: Rechargeable Lithium Polymer battery

Capacity: 600mAh

Rated cycle life: 300 cycles > 70% of initial cap Interface Antenna: omni-directional antenna

#### **User Interface**

Two call buttons and a menu button
Two red/green signal LEDs
Safety switch for lanyard
Customizable Alarms
Organic LED Display for text messaging and menu
Customizable Display Menu

#### Certifications

FCC Part 15 (US), IC (Canada), CE Mark (European Union)

#### Frequency Band

Channels 1-11: North America

Channels 1-13: Global Channels 1-14: Japan

#### Environment

Operating temperature: 32 to 122 °F / 0 to 50°C Storage temperature: -40 to 140 °F / -40 to 60 °C Humidity: 95 % non-condensing, relative humidity

Protection: splash proof enclosure

#### Typical Operating Range

Open Space: 330ft/100m @11Mbit/s,

500ft/150m @2Mbit/s

Closed Office: 140ft/40m @11Mbit/s.

200ft/60m @2Mbit/s

#### **Physical**

Dimensions: 2.36 x 3.54 x 0.33 in / 60 x 90 x 8.5 mm

Weight: 1.7 oz/ 46 g

Specifications subject to change without prior notice.



Ekahau East Coast (Headquarters) 1851 Alexander Bell Drive Suite 105 Reston, VA 20191 Tel: 1-866-4EKAHAU Fax: 1-703-860-2028 Ekahau Europe (Sales, R&D, Product Management) Hillikatu 3 00180 Helsinki, Finland Tel: +358-20-743 5910 Fax: +358-20-743 5919 sales-europe@ekahau.com Ekahau APAC (Regional office) B38, Tower 8, Imperial Cullinan 10 Hoi Fai Road, Tai Kok Tsui Hong Kong Tel: +852 9227 8406 sales-asia@ekahau.com

Global Tech Support: www.ekahau.com/support

www.ekahau.com

sales-americas@ekahau.com